





Faster Heating & Cooling Rate



Smart Phone App Available



More Durable Structure Design



User Friendly Interface





PRODUCT FEATURES





A new generation of CPU, 8-inch responsive touch screen, and user-friendly UI design makes your

operation simple and faster.



Temperature Accuracy



Newly-designed block and tailor-made peltier to ensure exceptional thermal performance and optimize your PCR temperature with good accuracy.



Mobile App Sync



Innovative mobile app and WiFi capability helps to monitor your PCR status with remote control.

REMOTE OPERATION INTERFACE



Remote Operation Interface on Mobile Phone App





Operation Interface on Device

PRODUCT PARAMETER

Model Name	GeneExplorer			
Product Code	BYQ6617E	BYQ6640E	BYQ6627E	BYQ6631E
Model	GE-96G	GE-48D	GE-48DS	GE-48D
Sample Capacity	96×0.2ml	48x0.2ml 2Blocks	48x0.2ml 2Blocks 3zonesx2	48×0.2ml+48×0.2ml
Temp. Range	4~105°C (min. resolution: 0.1°C)			
Max. Heatine Rate	6°C/sec			
Max. Cooling Rate	5.5°C/sec			
Temp. Uniformity	≤±0.2°C			
Temp. Accuracy	≤±0.2°C (30s after reaching 55 , 72 and 95°C respectively)			
Hot-lid Temp. Range	30°C~110°C			
Gradient Temp. Range	1-30°C	1-30℃	_	_
Max. Cycle Number	≥99, suitable for Nested PCR			
Time up / down	0~9m59s , suitable for Long PCR			
Temp. up / down	0.1∼9.9°C , suitable for Touchdown PCR			
Memory	≥2000 programs on board , unlimited with USB flash drive expansion			
Network Connections	USB / LAN / WIFI			
Hot-lid Mode	One-time locking with handle			
Mobile App Compatibility	iOS / Android			
Power Supply	100~240v , 50~60Hz , 600W			
Dimension	420mm×269mm×254mm (L×W×H)			
Net Weight	10.5kg			

^{*}Data tested at standard laboratories.



Address: 1192 Bin an Road, Hi-tech (Binjiang) District, Hangzhou, 310053, P.R.China Direct Phone: +86-571-87774575 (Overseas Department) Fax: +86-571-87774553 Homepage: http://www.bioer.com.cn Email: overseas@bioer.com.cn